

Five Islands Lighthouse Park

Additional Specifications

Lantern Room

- .1 Glass – 30" x 60" x 0.25" single pane
- .2 Roofing – 26 ga Safety Red steel shingles to resemble existing, contractor to provide sample for approval.
- .3 Railing – 1.25" OD Stainless Steel, painted Safety Red. To match original drawings.
- .4 Lantern – Original lantern fixture to be preserved and placed in rebuilt lantern room.
- .5 Counter – Replace original steel covered counter in lantern room with two layers of ¾" plywood, paint red to resemble existing.
- .6 Exterior lantern floor deck to be covered with slip-resistant, weatherproof material. (EPDM, Modified Bitumen or equivalent)
- .7 Chimney/Ventilator – Original ventilator/chimney cap to be preserved and reinstalled on new roof of lantern room.
- .8 Exterior trims – To match existing and painted white.

Siding

- .1 Sheathing – 1.25" x 4.375" Tongue and Groove, placed diagonally.
- .2 Weather proofing – CSA approved rain screen for shingle installation and CSA approved sheathing membrane.
- .3 Shingles – Clear grade, Eastern Cedar, 4.5" exposure, pre-stained on all sides
- .4 Flashings – Custom, zinc flashing to be used where necessary

Paint & Stain

- .1 White Paint – Benjamin Moore HP 2200, Alkyd Urethane Enamel, Colour: Super White
- .2 Red Paint – Benjamin Moore HP 2200, Alkyd Urethane Enamel, Colour: Safety Red
- .3 Stain – Peintures MF ISO-STAIN, 100% Acrylic, Solid Stain, Colour: Super White